

Your advantages at a glance.

STARstrap™-plus - available in widths ranging between 15.5mm and 32mm
- its special features being its splicing resistance, very high sealing strength and tough edge rigidity.

STARstrap™-plus - can be used for particularly difficult applications.

STARstrap™-plus - an alternative to steel strapping up to 32mm thick.

STARstrap™-plus - is particularly suited for automated applications.

STARstrap™-plus - will give your products better protection compared with steel strapping.



Common steel strapping with edge protection



STARstrap™-plus - the new generation - often requires no edge protection

FROMMM | PACKAGING SYSTEMS

STARstrap™-plus- polyester strapping for the timber industry



strapping dimension for the timber industry

Dimension	Surface	Green	Black
15,5 x 0,9mm	embossed / plain	x / x	x / x
16,0 x 0,8mm	embossed	x	x
16,0 x 1,0mm	embossed / plain	x / x	x / x
19,0 x 0,8mm	embossed / plain	x / x	x / x
19,0 x 1,0mm	embossed / plain	x / x	x / x
19,0 x 1,27mm	embossed / plain	x / x	x / x
19,0 x 1,35mm	plain	x	x
19,0 x 1,53mm	plain	x	x
25,0 x 0,8mm	embossed	x	x
25,0 x 1,0mm	plain	x	x
32,0 x 0,6mm	plain	x	x
32,0 x 0,8mm	plain	x	x
32,0 x 1,0mm	plain	x	x
32,0 x 1,2mm	plain	x	x



All dimensions are of course also available as jumbo rolls.
Precise roll lengths available on request.